

PlusGuard 7 Series: 10 AMPS

The PlusGuard 7-10A is a multi-outlet design Voltage Protector rated at 10 Amps, prevents damages to electrical and electronic equipment from power fluctuation, especially over and under voltage levels of long duration. The 6 sec / 180 sec delay reconnection provides protection against power-back surge commonly experienced after resumption of power in a power cut situation. Build-in MOV excess electricity for additional protection. The PlusGuard 7-10A will automatically guard your equipment against brownouts or transient spikes induced by lighting or power line failure.



- > Microprocessor Controlled Design
- > Grounded Multi-outlet Design
- > Surge Suppression 900 Joules
- > Delay Reconnection Selector 6 sec / 180 sec
- > Provide Overload Protection
- > Wall Mountable

Specifications:

MODEL	PlusGuard 7-10A
INPUT	
Max. Current	10 Amps
Nominal Voltage	110 - 120Vac
Frequency	50Hz or 60Hz
Input Line Low Loss (@110Vac)	90Vac
Input Line Low Comeback (@110Vac)	95Vac
Input Line High Loss (@110Vac)	140Vac
Input Line High Comeback (@110Vac)	137Vac
Spike Protection	900 Joules
Connectors	Nema5-15P
OUTPUT	
Nominal Voltage	110 - 120Vac
Frequency	50Hz or 60Hz
Delay Timer	6 sec / 180 sec
Connectors	Nema5-15R*4pcs
INDICATOR	
LED	3 LEDs
ENVIRONMENT	
Operating Temperature	0°C - 40°C (32°F - 104°F)
Humidity	0 - 95% (Non-condensing)
Acoustic Noise	< 40dB at 1M

*Product specifications are subject to change without further notice.