

PlusGuard 8 Series: 10 AMPS

The PlusGuard 8-10A is a multi-outlet design Voltage Protector rated at 10 Amps, prevents damages to electrical and electronic equipment from power fluctuation, especially over and under voltage levels of long duration. The 6 sec / 180 sec delay reconnection provides protection against power-back surge commonly experienced after resumption of power in a power cut situation. Build-in MOV excess electricity for additional protection. The PlusGuard 8-10A will automatically guard your equipment against brownouts or transient spikes induced by lighting or power line failure.



- > Microprocessor Controlled Design
- > Grounded Multi-outlet Design
- > Surge Suppression 900 Joules
- > Delay Reconnection Selector 6 sec / 180 sec
- > Provide Overload Protection
- > Wall Mountable

Specifications:

| MODEL | PlusGuard 8-10A |
|------------------------------------|---------------------------|
| INPUT | |
| Max. Current | 10 Amps |
| Nominal Voltage | 220 - 240Vac |
| Frequency | 50Hz or 60Hz |
| Input Line Low Loss (@220Vac) | 180Vac |
| Input Line Low Comeback (@220Vac) | 190Vac |
| Input Line High Loss (@220Vac) | 268Vac |
| Input Line High Comeback (@220Vac) | 260Vac |
| Spike Protection | 900 Joules |
| Connectors | Nema5-15P |
| OUTPUT | |
| Nominal Voltage | 220 - 240Vac |
| Frequency | 50Hz or 60Hz |
| Delay Timer | 6 sec / 180 sec |
| Connectors | EURO-US socket*4pcs |
| INDICATOR | |
| LED | 3 LEDs |
| ENVIRONMENT | |
| Operating Temperature | 0°C - 40°C (32°F - 104°F) |
| Humidity | 0 - 95% (Non-condensing) |
| Acoustic Noise | < 40dB at 1M |

*Product specifications are subject to change without further notice.